IN THE CLAIMS:

Please amend claims 1, 13, and 14. Please note that all claims currently pending and under consideration in the above-referenced application are shown below. Please enter these claims as amended. This listing of claims will replace all prior versions and listings of claims in the application.

Listing of Claims:

(Currently Amended) A composite article comprising:
 a pre-preg material comprising a reinforcement impregnated with a thermosetting resin, the composite article having a specific density ranging from approximately 1.00 g/ml to

wherein the composite article is configured as at least a component of a rocket nozzle.

approximately 1.15 g/ml, 1.15 g/ml,

- 2. (Original) The composite article of claim 1, wherein the thermosetting resin comprises a carbon phenolic resin.
- 3. (Original) The composite article of claim 1, wherein the thermosetting resin comprises a phenolic resin or an epoxy resin.
- 4. (Original) The composite article of claim 1, wherein the reinforcement comprises glass fibers, boron filaments, boron nitride, silicon carbide, graphite (carbon) filaments, or high modulus organic filaments.
- 5. (Original) The composite article of claim 4, wherein the high modulus organic filaments comprise poly(benzothiazoles) or poly(aromatic amides).
- 6. (Original) The composite article of claim 1, wherein the reinforcement comprises organic filaments of nylon, polyethylene, or aramid.

- 7. (Cancelled)
- 8. (Previously Presented) The composite article of claim 1, wherein the pre-preg material further comprises a filler material selected from the group consisting of carbon powder, powdered alumina trihydrate, and antimony oxide.
 - 9. (Cancelled)
 - 10. (Cancelled)
- 11. (Previously Presented) The composite article of claim 1, wherein the composite article has an across-ply tensile strength that ranges from about 1800 psig to about 3000 psig.
- 12. (Previously Presented) The composite article of claim 1, wherein the composite article has an across-ply tensile strength that ranges from about 1800 psig to about 2200 psig.
- 13. (Currently Amended) A composite article comprising:

 a pre-preg material comprising a reinforcement impregnated with a carbon phenolic resin, the composite article having a specific density ranging from approximately 1.00 g/ml to approximately 1.15 g/ml.1.15 g/ml,

 wherein the composite article is configured as at least a component of a rocket nozzle.
- 14. (Currently Amended) The composite article of claim 4, wherein the pre-preg material further comprises a filler material selected from the group consisting of carbon powder, powdered alumina trihydrate, or antimony and antimony oxide.